



## Up-ward pressure booster pump PB-series

### Features

- Low noise level : Using centrifugal impeller
- Constant pressure level : Adjust more advanced flow sensor
- Anti-rust : Through electric coating of casing, it is able to control rust
- Hot water application : It can be used up to 80°C
- Long lifetime : 60% reduced on-off pressure switch working ensures double lifetime

### Application

- Down-ward water booster for small house
- Low water pressure area in apartment from the roof top water tank

### Technical Data

Model	Power Source (Phase/V/Hz)	Output Power (W)	Max Head (m)	Capacity (LPM)	Bore (mm)
PB-138MA	1/220/60	135	12	40(Ht=0.5m)	15(1/2")or20(3/4")
PB-S250MA		250	15	55(Ht=0.5m)	20(3/4")
PB-350MA		350	21	65(Ht=0.5m)	15(1/2")or20(3/4")
PB-351MA		350	21	80(Ht=0.5m)	25(1")
PB-600MA		600	28	80(Ht=0.5m)	32(1 1/4")
PB-088EA	1/220/50	60	9	35(Ht=0.5m)	15(1/2")or20(3/4")
PB-S125EA		125	11	42(Ht=0.5m)	20(3/4")
PB-200EA		200	15	50(Ht=0.5m)	15(1/2")or20(3/4")
PB-201EA		200	15	65(Ht=0.5m)	25(1")
PB-400EA		400	20	75(Ht=0.5m)	32(1 1/4")

### Performance Curve

