

# PRO1 R SASO

7 YEARS  
WARRANTYWATER  
PLUSEXTERNAL  
TEMPERATURE  
REGULATIONDOUBLE SAFETY  
THERMOSTATMADE IN  
ITALYTITANSHIELD  
TECHNOLOGYHIGH EFFICIENCY  
INSULATION

## ADVANCED PERFORMANCE

- WaterPlus technology: up to 16 % more hot water available\*
- Compliant with top ESWH regulations

## FULL COMFORT

- External temperature setting
- Double safety thermostat

## EVERLASTING QUALITY

- Robust insulation material (polyurethane)
- Magnesium anode to fight corrosion
- High quality titanium enameled tank
- 7 years warranty

## EXCLUSIVE DESIGN





- Designed in Italy
- Modern shape with "Ariston wave"
- User-friendly interface with heating feedback
- Wall-hung



## 7 years warranty

\* Maximum estimated saving, depending on models. Comparison made using V40 test results at maximum operating temperature between current ATG products and new ATG products equipped with WaterPlus Technology.

TECHNICAL DATA		PRO1 R SASO 50 V	PRO1 R SASO 80 V	PRO1 R SASO 100 V	PRO1 R SASO 50 H	PRO1 R SASO 80 H	PRO1 R SASO 100 H
Capacity	l	50	80	100	50	80	100
Installation	V		V	V	H	H	H
Size		Regular	Regular	Regular	Regular	Regular	Regular
Power	kW	1,2	1,5	1,8	1,2	1,5	1,5
Voltage	V	220	220	220	220	220	220
Heating time ( $\Delta T=45^{\circ}\text{C}$ )	h,min	2,11'	2,37'	2,46'	2,11'	2,37'	3,19'
Heat dispersion at $65^{\circ}\text{C}$	kWh/24h	0,99	1,35	1,56	1,2	1,48	1,65
Max working pressure	bar	8	8	8	8	8	8
Max working temperature	$^{\circ}\text{C}$	75	75	75	75	75	75
Weight	kg	17	22	26	17	22	26
Class	IP	IPX3	IPX3	IPX3	IPX1	IPX1	IPX1
OVERALL DIMENSIONS							
a	mm	543	748	900	543	748	900
b	mm	380	585	737	-	-	-
c	mm	-	-	-	163	178	178
d	mm	-	-	-	160	335	487
CODE							
		3201804	3201805	3201806	3201807	3201808	3201809



## LEGEND

- E** Cold water inlet G 1/2"
- U** Hot water outlet G 1/2"